Titan Cable Management (TCM) Rack



The Titan Cable Management rack (**TCM**) is a high density, open architecture cable management system that establishes pathways for large volume network cabling. Our data center cable management rack conveniently provides complete accessibility for cabling swaps and add-ons while also providing optimal heat dissipation. Our data center components allow your network hardware to run cooler and perform as intended.

Specifications:

Certified Load Rating of 2,100 lbs.

Heights: 45U, 51U

Mounting Widths: 19", 23"

• Depths: 6", 10", 16", 30"

ROHS Compliant

ISO9001 Certified

- Vented doors with dual handles for LH/RH access to equipment
- Third rail option for shallower equipment mounting into deeper racks
- #12-24 spare hardware for 6", 10" and 16" depth racks
- M6 square hardware for the 30" depth
- Baffle kit option
- Available in 11 standard colors
- Custom branding
- Ten year warranty

RU Height	Overall Height 6" Depth		10" Depth	16" Depth	30" Depth		
51	94.18"	TCMR-51U-6	TCMR-51U-10	TCMR-51U-16	TCMR-51U-30		
45	83.68"	TCMR-45U-6	TCMR-45U-10	TCMR-45U-16	TCMR-45U-30		


How to Specify Color

- For Black add "-116" to the end of the part number. For example: TCMR-51U-6-116
- For White add "-151" to the end of the part number.
 For example: TCMR-51U-6-151

Features:

- · Large vent pattern in rack sides help heat dissipation
- •#12-24 hardware for 6", 10" and 16" depth racks, M6 hardware for the 30" depth
- Stocked in standard black and white with a durable powder coat finish or available in nine additional standard colors (additional lead time)

Cabinet Color Options:



AMCO Enclosures offers standard color choices (up to 2 per console) for no extra charge. Custom colors are available and quoted upon request.

Estimated Cable Fill Capacities for TCM Frame

	Recommended Fill			Maximum Cable Fill								
Part Number	Description	Usable Area	Cat 5e	Cat 6	Cat 6a	2091SD	2091B	Cat 5e	Cat 6	Cat 6a	2091SD	2091B
r art Humber	Description	(sq. in.)	0.200	0.250	0.300	0.265	0.285	0.200	0.250	0.300	0.265	0.285
			40%	40%	40%	40%	40%	60%	60%	60%	60%	60%
TCMR-xxU-30	TITAN CABLE MANAGEMENT RACK 30"D	175.0	1114	713	495	635	549	1671	1070	743	952	823
TCMR-xxU-16	TITAN CABLE MANAGEMENT RACK 16"D	94.0	598	383	266	341	295	898	574	399	511	442
TCMR-xxU-10	TITAN CABLE MANAGEMENT RACK 10"D	60.3	384	245	170	218	189	575	368	256	328	283
TCMR-xxU-6	TITAN CABLE MANAGEMENT RACK 6"D	36.8	234	150	104	133	115	351	225	156	200	173

Note: The fill rates listed are at 40% and 60%.



Titan Cable Management (TCM) Rack



Cable Manager with Door

Vertical Cable Manager with Door


- TCM cable manager doors have a solid face with hidden hinges that feature easy on/off access to cabling
- Comes standard with 7.25" depth metal fingers with 2RU (3.50") or 1RU spacing
- Vertical cable managers are available in two widths 6" and 10" in either a 51RU or 45RU rack height; 12" and 16" wide are available as custom sizes with additional lead time

RU Height	Overall Height	Finger Spacing	6" Width	10" Width			
51	89.00"	2RU	TCMFD-51U-6	TCMFD-51U-10			
45	78.50" 2RU		TCMFD-45U-6	TCMFD-45U-10			
51	89.00"	1RU	TCMFD-1-51U-6	TCMFD-1-51U-10			
45	78.50"	1RU	TCMFD-1-45U-6	TCMFD-1-45U-10			

Note: TCMFD-1 part numbers have fingers at every RU

How to Specify Color

- For Black add "-116" to the end of the part number. For example: TCMFD-51U-6-116
- For White add "-151" to the end of the part number.
 For example: TCMFD-51U-6-151



2RU Finger Cable Manager 1RU Finger Cable Manager

2RU Finger Wire Cable Managers

Wire Cable Managers Metal fingers have a depth of 7.25" to accommodate larger cable bundles with a usable depth of 6" in 2RU designs for cable-routing requirements. 2RU fingers have a full 3.50" open spacing from finger center to finger center.

Estimated Cable Fill Capacities for TCM Cable Managers

		Usable Area	Recommended Fill					Maximum Cable Fill					
Part Number	Description		Cat 5e	Cat 6	Cat 6a	2091SD	2091B	Cat 5e	Cat 6	Cat 6a	2091SD	2091B	
r art Number	Description	(sq. in.)	0.200	0.250	0.300	0.265	0.285	0.200	0.250	0.300	0.265	0.285	
			40%	40%	40%	40%	40%	60%	60%	60%	60%	60%	
TCMFD-xxU-16	FINGERS WITH DOOR 16"	167.0	1063	680	473	606	524	1595	1021	709	908	785	
TCMFD-xxU-12	FINGERS WITH DOOR 12"	118.0	751	481	334	428	370	1127	721	501	642	555	
TCMFD-xxU-10	FINGERS WITH DOOR 10"	97.0	618	395	274	352	304	926	593	412	528	456	
TCMFD-xxU-6	FINGERS WITH DOOR 6"	41.0	261	167	116	149	129	392	251	174	223	193	

Note: The fill rates listed are at 40% and 60%. 12" and 16" wide are available as custom sizes with additional lead time.

