

Titan ZN4 - Data



Seismic Zone 4 Series Features

- Certified to Telcordia Specification NEBS GR-63-CORE, Issue 4
- 1,200lb (544KG) Seismic Load Rating
- EIA Standard 310D
- Fully welded steel construction
- Floor mounting hardware (Hilti) available
- 11 standard colors or custom color matching available
- Tested and approved for seismic events up to 8.3 magnitude
- Full line of accessories
- 10 Year Warranty
- Made in the USA

24" Width Frames

RU Height	42" Depth
47	R-Z4-47U24-42
44	R-Z4-44U24-42
42	R-Z4-42U24-42

RU Height	36" Depth
47	R-Z4-47U24-36
44	R-Z4-44U24-36
42	R-Z4-42U24-36

Note: Mounting channels not included.

24" Width Frames 19" Panel Opening



Note: AMCO Enclosures offers standard color choices (up to 2 per console) for no extra charge. Custom colors are available and quoted upon request.

Doors



Curved Face

Vented Flush

French Flush

24" Width Curved-Face Door

RU Height	Vented
47	DK-CV-47U24
44	DK-CV-44U24
42	DK-CV-42U24

24" Width French Flush

RU Height	Vented	Door with Solid Insert
47	DFK-BFZ-47U24	DFK-BFZ-SPI-47U24
44	DFK-BFZ-44U24	DFK-BFZ-SPI-44U24
42	DFK-BFZ-42U24	DFK-BFZ-SPI-42U24

24" Width Flush Door

RU Height	Vented w/ Solid Insert	Vented
47	DSFL-TN-47U24	DVFL-TN-47U24
44	DSFL-TN-44U24	DVFL-TN-44U24
42	DSFL-TN-42U24	DVFL-TN-42U24

Titan ZN4 - Data



Mounting Channels



MX Mounting Channels

RU Height	MCX Mounting Channels-M6
47	MCX-TN-S-47U
44	MCX-TN-S-44U
42	MCX-TN-S-42U


Side Panels



Side Panel

RU Height	36" Depth	42" Depth
47	SPKS-47U-36	SPKS-47U-42
44	SPKS-44U-36	SPKS-44U-42
42	SPKS-42U-36	SPKS-42U-42

Note: Side panels are available in bolt-down version - specify at time of order placement.



Power/Cable Panel

Power/Cable Panel

- Tool-less mounting makes PDU mounting fast and easy
- Available in 5" and 10" widths



Cable Lacing Strip

Cable Lacing Strip

Available in four rack heights and a 5" width. Cable lacing strips have a combination of M6 holes for cable ring mounting (HK-CR1) while the slots can accept cable ties and T-bars for velcro straps.

Horizontal Cable Manager

HCM Panels have a 2RU panel height (3.50") and feature 10 ga. steel construction. Available in 4" and 7" depths.



Casters

Casters are available in two options. Heavy duty casters are used when moving a fully integrated rack and light duty casters are used when moving empty racks into position.

- Light duty -175 lbs. load rating
 - adds 1" to overall frame height
- Heavy duty -1,200 lbs. load rating
 - adds 1.75" to overall frame height

Hardware Kits

Each rack ships with 50 ea. HK M6 inserts and screws to make mounting hardware/components easy to install.

Square Hole Mounting Hardware Kits

HKM6-25 or -50 M6 hardware for equipment mounting. Includes 25 or 50 M6 mounted screws.

HKDZ-25- (25) M6 Metric Dzus easy inserts and M6 clear chromate screws.

Frame-Joining Hardware

HK-R-TN- Frame-joining kit (8 pieces)



Light Duty Caster
CA-C175



Heavy Duty Caster
CA-C1200



M6
HKM6-25



Dzus M6
HKDZ-25



Joining Kit
HK-R-TN