

Titan ZN4 - Electronics Packaging



Seismic Zone 4 Series Features

- Certified to Telcordia Specification NEBS GR-63-CORE, Issue 4
- 1,200lb (544KG) Seismic Load Rating
- EIA Standard 310D
- Fully welded steel construction
- Floor mounting hardware (Hilti) available
- 11 standard colors or custom color matching available
- Tested and approved for seismic events up to 8.3 magnitude
- Full line of accessories
- 10 Year Warranty
- Made in the USA

24" Width Frames

RU Height	36" Depth
45	R-Z4-45U24-36
40	R-Z4-40U24-36
35	R-Z4-35U24-36

RU Height	30" Depth
45	R-Z4-45U24-30
40	R-Z4-40U24-30
35	R-Z4-35U24-30

RU Height	25.5" Depth
45	R-Z4-45U24-255
40	R-Z4-40U24-255
35	R-Z4-35U24-255

Note: Mounting channels not included.


24" Width Frames 19" Panel Opening



Pottery White 101-T Light Blue 111-T Silver 112-T Gunmetal 113-T Black 116-T Pearl Gray 122-T Pebble Gray 123-T Light Beige 125-T Cranberry 126-T Medium Blue 816-T Glacier White XOP-151T

Note: AMCO Enclosures offers standard color choices (up to 2 per console) for no extra charge. Custom colors are available and quoted upon request.

Mounting Channels



MX Mounting Channels

MX Mounting Channels - Tapped

RU Height	MCX Mounting Channels-M6	MCX Mounting Channels-Tapped
45	MCX-TN-S-45U-PLT	MCX-TN-T-45U-PLT
40	MCX-TN-S-40U-PLT	MCX-TN-T-40U-PLT
35	MCX-TN-S-35U-PLT	MCX-TN-T-35U-PLT

Side Panel

RU Height	25.5" Depth	30" Depth	36" Depth*
45	SPKS-45U-255	SPKS-45U-30	SPKS-45U-36
40	SPKS-40U-255	SPKS-40U-30	SPKS-40U-36
35	SPKS-35U-255	SPKS-35U-30	SPKS-35U-36

Side Panels



Louvered Side Panel

Side Panel

Louvered Side Panel

RU Height	25.5" Depth	30" Depth	36" Depth*
45	SPKL-45U-255	SPKL-45U-30	SPKL-45U-36
40	SPKL-40U-255	SPKL-40U-30	SPKL-40U-36
35	SPKL-35U-255	SPKL-35U-30	SPKL-35U-36

Note: Side panels are available in bolt down version - specify at time of order placement. *36" depth side panels have two locks at the top vs. the 25.5" and 30" depth

Titan ZN4 - Electronics Packaging



Doors



Curved Face

Vented Flush

Vented Face

24" Width Curved-Face Door

RU Height	Polycarbonate	Solid	Vented
45	DK-CP-45U24	DK-CS-45U24	DK-CV-45U24
40	DK-CP-40U24	DK-CS-40U24	DK-CV-40U24
35	DK-CP-35U24	DK-CS-35U24	DK-CV-35U24

24" Width Square-Face Door

RU Height	Polycarbonate	Solid	Vented	Louvered
45	DPFA-TN-45U24	DSFA-TN-45U24	DVFA-TN-45U24	DLFA-TN-45U24
40	DPFA-TN-40U24	DSFA-TN-40U24	DVFA-TN-40U24	DLFA-TN-40U24
35	DPFA-TN-35U24	DSFA-TN-35U24	DVFA-TN-35U24	DLFA-TN-35U24

24" Width Flush Door

RU Height	Polycarbonate	Solid	Vented	Louvered
45	DPFL-TN-45U24	DSFL-TN-45U24	DVFL-TN-45U24	DLFL-TN-45U24
40	DPFL-TN-40U24	DSFL-TN-40U24	DVFL-TN-40U24	DLFL-TN-40U24
35	DPFL-TN-35U24	DSFL-TN-35U24	DVFL-TN-35U24	DLFL-TN-35U24



Cable Lacing Strip

Available in four rack heights and a 5" width. Cable lacing strips have a combination of M6 holes for cable ring mounting (HK-CR1) while the slots can accept cable ties and T-bars for velcro straps.


Cable Lacing Strip

Horizontal Cable Manager

HCM Panels have a 2RU panel height (3.50") and feature 10 ga. steel construction. Available in 4" and 7" depths.



Light Duty Caster
CA-C175



Heavy Duty Caster
CA-C1200

Casters

Casters are available in two options. Heavy duty casters are used when moving a fully integrated rack and light duty casters are used when moving empty racks into position.

- Light duty -175 lbs. load rating
 - adds 1" to overall frame height
- Heavy duty -1,200 lbs. load rating
 - adds 1.75" to overall frame height



M6
HKM6-25



Dzus M6
HKDZ-25

Hardware Kits

Each rack ships with 50 ea. HK M6 inserts and screws to make mounting hardware/components easy to install.

Square Hole Mounting Hardware Kits

HKM6-25 or -50 M6 hardware for equipment mounting. Includes 25 or 50 M6 mounted screws.

HKDZ-25- (25) M6 Metric Dzus easy inserts and M6 clear chromate screws.

Frame-Joining Hardware

HK-R-TN- Frame-joining kit (8 pieces)



Joining Kit
HK-R-TN